

KUMHO PETROCHEMICAL

KUMHO BLDG 57, 15TH & 16TH FL, 57 SHINMMUNRO, 1-KA, CHONGNO-KU, SEOUL 110-061 KR

ABS-750SW**Acrylonitrile Butadiene Styrene (ABS), furnished as pellets**

Color	Min Thk	Flame	HMI	HAI	RTI	RTI	RTI
	(mm)	Class			Elec	Imp	Str
ALL	1.5	HB	3	0	60	60	60
	3.0	HB	2	0	60	60	60
Comparative Tracking Index (CTI): 0				Dimensional Stability (%): -			
High-Voltage Arc Tracking Rate (HVTR): 2				High Volt, Low Current Arc Resis (D495): 6			
Dielectric Strength (kV/mm): -				Volume Resistivity (10^X ohm-cm): -			

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Report Date: 1981-03-24

Last Revised: 2005-03-08

Underwriters Laboratories Inc®

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thickness	Value
		Class (color)	Tested (mm)	
IEC Flammability	IEC 60695-11-10		1.5	HB75 (ALL)
			3.0	HB40 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-

Underwriters Laboratories Inc®